



Rev 0
07/22



TEKNOIL RAPID

Disarming for quick scasserature and deformation



DESCRIPTION

TEKNOIL RAPID is a disarming agent specially formulated for the rapid dismantling and demoulding of cementitious products. The high degree of lubricity of the product allows to obtain a perfect cleaning of the formwork or formwork, whether they are in iron or fiberglass. The perfect disarmament allows to obtain artifacts with excellent surface finish, avoiding, as happens with other types of disarming unsuitable, to have either falls of edges or an imperfect return of the artifact from the formwork.

FIELDS OF APPLICATION

Particularly suitable for all types of instant processing of artifacts, for concrete castings in metal formwork intended for the production of small and medium-sized products.

ADVANTAGES

TEKNOIL RAPID guarantees and facilitates the detachment of the products from the formwork ensuring a good level of finish.

MODE OF USE

TEKNOIL RAPID can be applied by spray or brush.

EQUIPMENT

For the application of our disarming, quickly and extremely economically, we have prepared special equipment.

Our Technical Department is at your disposal to evaluate the equipment that best suits your needs.

PHYSICAL PROPERTIES

	Clear liquid state
Density (at 15°C)	0,814 ± 0.02 kg/l
Flash point	84°C
Self-flammability	> 200°C
Solubility in	insoluble water
Solubility in	soluble organic solvents

DOSAGE

Since the product is multipurpose for several types of products, if it is too concentrated, we recommend diluting a part of TEKNOIL RAPID in 15+20 parts of petroleum solvents (diesel, kerosene, white water).

SHEET



TEKNA CHEM S.p.A.

Factory: Renate (MB) - Via Sirtori, z.i. 20838 - Tel. +39 0362.91.83.11

Web: www.teknachemgroup.com - E-mail: info@teknachemgroup.com - Fax: +39 0362.91.93.96



CONSUMPTION

Under normal conditions you can treat 60÷70 square meters of surface with 1 liter of TEKNOIL RAPID.

PACKS

- Tank of 1050 lt.
- Drum of 210 lt.
- Tank of 25 lt.

STORAGE

The product can be stored for a long time, in the original packaging, in covered places. Store the product away from heat sources.

TECHNICAL SERVICE

Our technical service is at your complete disposal to provide detailed technical instructions on the use of the products.

WARNINGS

Use according to the instructions on the technical and safety data sheet. Use complete protective clothing.

Consult the toxicology sheet.

LEGAL

The information contained in this technical sheet, although representing the most advanced stage of knowledge, does not exempt the user from performing accurate preliminary tests in their conditions of use and operation. We therefore decline any responsibility for the improper use of the product.

